


| PIN | Assignment |
|-----|------------|
| 1 | X1 |
| 2 | Y1 |
| 3 | X2 |
| 4 | Y2 |



Notes:

- | | |
|---|---|
| 1. Type: Film to Glass | 2. Operating Voltage: $\leq 10V$ |
| 3. Operation Temperature: $-10^{\circ}C \sim 60^{\circ}C$ | Storage Temperature: $-20^{\circ}C \sim 70^{\circ}C$ |
| 4. Life Time: $> 1,000,000$ times | 5. Connect Material: FPC |
| 6. Response Time: $\leq 10ms$ | 7. Linearity: $\leq 1.5\%$ |
| 8. Transmittance: $\geq 75\%$ | 9. Surface Hardness $\geq 3H$ (pencil) |
| 10. Operation force: $60g \sim 120g$ | 11. Resistance: Y: $200\Omega - 600\Omega$ X: $300\Omega - 800\Omega$ |

| | | | |
|------------------------------------|-------------------|------------|-----------|
| OBEY CO., LIMITED | | | |
| WWW.OBTOUCH.COM WWW.OBEYCROP.COM | | | |
| MODEL NO. | TS165A4K01 | UNIT: | MM |
| DRAWN: | | TOLERANCE: | ± 0.3 |
| DATE: | | SCALE: | 1:1 |
| VERSION: | 1.0 | REV: | |