



Instruction:

1. Type: Film to Glass
2. Operating Voltage: ≤10V
3. Response Time: ≤10ms
4. Storage Temperature: -20°C ~ +70°C
5. Operation Temperature/Humidity: -10°C ~ +60°C / 20% ~ 95%
6. Hitting Life: >10,000,000 Times, 250gf Force;
7. Writing Life: >1,000,000 Times 250gf Force;
8. Connect Material: FPC+PIN

9. Film Thickness: 0.188mm
10. Glass Thickness: 1.8mm
11. Light transmission: ≥78%
12. Force: 100g or more
13. Linearity: ≤5%
14. Insulation: ≥20MΩ
15. Resistance: 50Ω < PIN1, PIN2 < 250Ω
50Ω < PIN2, PIN4 < 250Ω
50Ω < PIN4, PIN5 < 250Ω
50Ω < PIN5, PIN1 < 250Ω
16. Surface Hardness ≥3H (pencil)

OBEY CO., LIMITED

WWW.OBTOUCH.COM | WWW.OBEYCROP.COM

MODEL NO.	TS156A5K02	UNIT:	MM
DRAWN:		TOLERANCE:	±0.3
DATE:	15/1/2	SCALE:	1:1
VERSION:	1.0	REV:	TP156W5L1